

THICKNESS: 0.83 in (21 mm)
AREAL DENSITY: 11.05 lb/ft²

4403MC



SHOOTER CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
4403MC-SH-MC-L	10.00 x 12.00 in (254 x 305 mm)	7.7 lb (3.5 kg)

SAPI CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
4403MC-SA-MC-XL	11.00 x 14.00 in (279 x 356 mm)	10.7 lb (4.9 kg)
4403MC-SA-MC-L	10.25 x 13.25 in (260 x 337 mm)	9.1 lb (4.2 kg)
4403MC-SA-MC-M	9.50 x 12.50 in (241 x 318 mm)	7.9 lb (3.6 kg)
4403MC-SA-MC-S	8.75 x 11.75 in (222 x 298 mm)	6.9 lb (3.1 kg)

MODEL 4403MC THREAT PERFORMANCE MATRIX

	LEAD CORE					MILD STEEL CORE			ENHNC PERF	ARMOR PIERCING CORE		
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	7.62 x 51 mm - M80 Max Velocity 2810 ft/s (856 m/s)	7.62 x 63 mm - J5P Max Velocity 2794 ft/s (852 m/s)	5.56 x 45 mm - M855 (SS109) Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - LP5 Max Velocity 2832 ft/s (863 m/s)	7.62 x 39 mm - M855A1 Max Velocity 3180 ft/s (969 m/s)	7.62 x 39 mm - API Max Velocity 2410 ft/s (735 m/s)	7.62 x 51 mm - B-32 - API Max Velocity 2850 ft/s (869 m/s)	7.62 x 51 mm - M61 Max Velocity 2830 ft/s (863 m/s)	7.62 x 63 mm - AP M2 Max Velocity 2910 ft/s (887 m/s)
4403MC-SH-MC-XL	6	6	3	1	6	3	1	3	3	1	1	1
4403MC-SA-MC-XL	6	6	3	1	6	3	1	3	3	1	1	1
4403MC-SA-MC-L	6	6	3	1	6	3	1	3	3	1	1	1
4403MC-SA-MC-M	6	6	3	1	6	3	1	3	3	1	1	1
4403MC-SA-MC-S	3	3	3	1	6	3	1	3	3	1	1	1

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

© 2025 Hesco. All rights reserved.

