

MODEL L211 BALLISTIC INSERTS

SPECIAL RIFLE THREATS • STAND ALONE

L211



THICKNESS: 0.69 in (17 mm)
AREAL DENSITY: 6.96 lb/ft²

SHOOTER CUT - SINGLE CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
L211-SH-SC-L	10.00 x 12.00 in (254 x 305 mm)	4.9 lb (2.2 kg)

MODEL L211 THREAT PERFORMANCE MATRIX

	LEAD CORE				MILD STEEL CORE		ENHNCD PERF	ARMOR PIERCING CORE
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	7.62 x 54R - LP5 Max Velocity 2832 ft/s (863 m/s)	5.56 x 45 mm - M855A1 Max Velocity 3180 ft/s (969 m/s)	7.62 x 39 mm - API Max Velocity 2410 ft/s (735 m/s)	
L211-SH-SC-L	6	6	6	6	3	3	3	

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

© 2025 Hesco. All rights reserved.

