

3110



THICKNESS: 1.09 in (28 mm)
AREAL DENSITY: 7.76 lb/ft²

SIDE PLATES - SINGLE CURVE

PART NUMBER	WIDTH x LENGTH	WEIGHT
3110-SP-SC-L	6.00 x 8.00 in (152 x 203 mm)	2.3 lb (1.0 kg)
3110-SP-SC-S	6.00 x 6.00 in (152 x 152 mm)	1.6 lb (0.7 kg)

Also available in LV (ICW) version.

MODEL 3110 THREAT PERFORMANCE MATRIX

	LEAD CORE					MILD STEEL CORE			ENHNC'D PERF	ARMOR PRC'ING CORE
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	7.62 x 51 mm - M80 Max Velocity 2810 ft/s (856 m/s)	7.62 x 63 mm - JSP Max Velocity 2794 ft/s (852 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	7.62 x 54R - LPS Max Velocity 2832 ft/s (863 m/s)	5.56 x 45 mm - M855A1 Max Velocity 3180 ft/s (969 m/s)	7.62 x 39 mm - API Max Velocity 2410 ft/s (735 m/s)	
3110-SP-SC-L	1	1	1	1	1	1	1	1	1	
3110-SP-SC-S	1	1	1	1	1	1	1	1	1	

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

© 2026 Hesco. All rights reserved.

